

**ICHIRO**

ICHIRO BYAKKO ICR-5403

Description

説明

Automatic Transmission Fluid formulated with selected fully synthetic base stocks and latest additive technology available that provides excellent service in applications calling for low and ultra low viscosity ATF, such as: Toyota Type WS, Nissan Matic S and Hyundai SP-IV.

With the use of fully synthetic base stocks and stability of this finished oil, these helps in protecting against thermal breakdown at high operating temperatures, while still providing outstanding performance at ambient temperatures as low as -45° C. Moreover, it improves overall transmission durability and cleanliness.

Benefits

特典

- △ Provides excellent oxidation and thermal stability for longer life.
- △ Superior wear protection to protect critical transmission components.
- △ Application in low viscosity & ultra low viscosity auto transmission.
- △ Excellent rust and corrosion protection.

Typical Characteristics

典型的な特徴

Test Description	Method	Unit	ICR- 5403
Density @ 15 °C	ASTM D 4052	kg/L	0.845
Flash Point	ASTM D 92	°C	198
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	26.72
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	5.66
Viscosity Index	ASTM D 2270	-	160
Appearance	Visual	-	Red



Specifications & Recommendations

仕様と推奨事項

△ AISIN	JWS 3324 ATF, ATF-0WS	SFU
△ ATF	134	SFU
△ ATF	3353	SFU
△ ATF	DVI	SFU
△ ATF	L12108	SFU
△ ATF	M-1375.4	SFU
△ ATF	M-1375.6	SFU
△ Bentley	P/N PY112995PA	SFU
△ BMW	ATF 3+	SFU
△ BMW	ATF 6	SFU
△ BMW	M-L12108	SFU
△ BMW	P/N 83 22 0 142 516	SFU
△ BMW	P/N 83 22 0 397 114	SFU
△ BMW	P/N 83 22 2 152 426	SFU
△ BMW	P/N 83 22 2 163 514	SFU
△ BMW	P/N 83 22 2 289 720	SFU
△ BMW	P/N 83 22 2 305 396	SFU
△ BMW	P/N 83 22 2 305 397	SFU
△ BMW	P/N 83 22 2 355 599	SFU
△ BMW	P/N 83 22 2 355 601	SFU
△ FCA	8 & 9 Speed ATF, P/N 68218925AA/AB	SFU
△ FCA	AW-1, P/N 68092912AA	SFU
△ FCA	Fiat 9.55550-AV2	SFU
△ FCA	Fiat 9.55550-AV5	SFU
△ FCA	Fiat 9.55550-AV6	SFU
△ FCA	P/N 05127382	SFU
△ FCA	P/N 68157995AA/AB	SFU
△ FCA	SP-IV, P/N 68171866AA	SFU
△ FCA	SP-IV, P/N 68171869AA	SFU
△ Ford	P/N XT-6-QSP	SFU
△ Ford	P/N XT-10-QLV	SFU
△ GM	AW1, P/N 19256039	SFU
△ GM	Dex HP [GMW 16974]	SFU
△ GM	WS, P/N 88863400	SFU
△ GM	WS, P/N 88863401	SFU
△ Honda / Acura	ATF DW-1 P/N (08200-9008)	SFU
△ Honda / Acura	ATF Type 3.0 (08200-9016-A)	SFU
△ Honda / Acura	ATF Type 3.1 (08200-9017)	SFU
△ Hyundai / Kia	ATF SP-IV	SFU
△ Hyundai / Kia	P/N 040000C90SG	SFU
△ Hyundai / Kia	SP4-M1	SFU
△ Hyundai / Kia	SPH-IV	SFU
△ Hyundai / Kia	SP-IV	SFU
△ Hyundai / Kia	SP-IV-RR	SFU
△ Hyundai / Kia	WS, spec NWS-9638	SFU

Specifications & Recommendations

仕様と推奨事項

△ Isuzu	ATF WSI	SFU
△ Isuzu	SCS	SFU
△ Jaguar	02JDE 26444	SFU
△ Jaguar	Fluid 8432	SFU
△ JAMA	JASO M315, Class 1-A-LV(1)	SFU
△ Land Rover	AW-1 P/N LR0022460: LV	SFU
△ Land Rover	LR 023288/023289	SFU
△ Land Rover	P/N TYK500050	SFU
△ Maserati	Oil No. 231603	SFU
△ Mazda	ATF FZ	SFU
△ Mercedes	MB 236.12	SFU
△ Mercedes	MB 236.14	SFU
△ Mercedes	MB 236.41	SFU
△ Mitsubishi	ATF-J3	SFU
△ Mitsubishi	Dia Queen ATF-MA1, P/N MZ320775	SFU
△ Mitsubishi	Dia Queen ATF-PA, P/N 4030401	SFU
△ Mitsubishi	SP-IV	SFU
△ Nissan	Matic R, P/N 999MP-MTR00P	SFU
△ Nissan	Matic S, P/N 999MP-MTS00P	SFU
△ Nissan	Matic W	SFU
△ Porsche	P/N 000 043 304 00	SFU
△ Porsche	P/N 000 043 304 01	SFU
△ Porsche	P/N 000 043 305 43	SFU
△ Porsche	P/N 000 043 305 54	SFU
△ Porsche	P/N 000 043 306 24	SFU
△ Porsche	P/N 958 300 540 00	SFU
△ Saab	P/N 93 165 147	SFU
△ Subaru	ATF-WS	SFU
△ Suzuki	Matic S	SFU
△ Toyota	ATF FZ	SFU
△ Toyota	JWS 3324, ATF WS (or NWS9638)	SFU
△ Volvo	P/N 31 256 774, 31 256 775	SFU
△ Volkswagen / Audi	G 052 533	SFU
△ Volkswagen / Audi	G 055 005 A2	SFU
△ Volkswagen / Audi	G 055 162 A2 or A6	SFU
△ Volkswagen / Audi	G 055 540 A2	SFU
△ Volkswagen / Audi	G 060 162 A2	SFU
△ ZF	LifeguardFluid 6 (ZF No. S671 090 255)	SFU
△ ZF	LifeguardFluid 8 (ZF No. S671 090 312)	SFU
△ ZF	LifeguardFluid 9 (ZF No. AA01.500.001)	SFU

最後の変更: 28/6/2024
整理番号: 5392G3ATFREV1