

**ICHIRO**

ICHIRO BYAKKO ICR-5411

Description

説明

Continuously Variable Transmission Fluid blended from high-performance fully synthetic base oils and carefully selected additives, including friction modifiers, detergent-dispersants, oxidation inhibitors, viscosity index improvers, corrosion inhibitors, and defoaming agents.

This oil is an automatic transmission well-balanced fluid specially designed for use in latest generations of Continuously Variable Transmissions (CVT) which transfer traction via steel-made traction chains or belts. It provides outstanding power transmission ratios and better fuel-economy performance of CVTs as compared with the regular automatic transmissions, many car makers have been adopting CVTs in more and more models.

Benefits

特典

- △ Excellent low temperature fluidity, reducing start up wear
- △ Provides excellent friction, oxidation and thermal stability
- △ Outstanding anti-wear properties and oil film thickness
- △ Compatible with a wide range of seals

Typical Characteristics

典型的な特徴

Test Description	Method	Unit	ICR- 5411
Density @ 15 °C	ASTM D 4052	kg/L	0.839
Flash Point	ASTM D 92	°C	198
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	26.18
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	6.201
Viscosity Index	ASTM D 2270	-	201
Appearance	Visual	-	Green / Neutral

Specifications & Recommendations

仕様と推奨事項

△ AUDI/ VW	P/N G 052 180 (-A2)
△ AUDI/ VW	P/N G 052 516 A2
△ CHRYSLER FCA	MOPAR CVTF+4 P/N 05191184A
△ CHERY	CVTF WCF-1
△ DAIHATSU	AMMIX CVTF- DFE
△ DAIHATSU	AMMIX CVTF- DTC
△ DODGE/ JEEP	NS-2
△ FCA	CVTF+4 P/N 05191184AA
△ GM	CVTF I-GREEN2
△ GM	HP-CVT P/N19355873
△ GM	P/N 19260800
△ HONDA	HCF-2 P/N 08200-HCF2
△ HYUNDAI / KIA	SP-CVT 1
△ MAZDA	CVTF 3320
△ MITSUBISHI	DIAMOND GREEN CVTF-J1
△ MITSUBISHI	DIAMOND GREEN CVTF-J4
△ NISSAN	NS-1
△ NISSAN	NS-2
△ NISSAN	NS-3
△ RENAULT	ELFMATIC
△ SHELL	GREEN 1V
△ SUBARU	LINEARTRONIC CVTF
△ SUBARU	LINEARTRONIC CV-30; P/N K0425Y0710
△ SUBARU	LINEARTRONIC CVTF-II; P/N K0425Y0711
△ SUBARU	e-CVT
△ SUBARU	i-CVT
△ SUBARU	HIGH TORQUE P/N K0421Y0700
△ SUZUKI	CVT FLUID GREEN 1
△ SUZUKI	CVT FLUID GREEN 2
△ SUZUKI	CVTF 3320
△ SUZUKI	NS-2
△ TOYOTA / LEXUS	FE
△ TOYOTA / LEXUS	TC

最後の変更: 28/6/2024

整理番号: 5800G3LONS3REV2