

**ICHIRO**

ICHIRO BYAKKO ICR-5306

Description

説明

Premium Synthetic Automatic Transmission fluid formulated with selected high viscosity index synthetic base stocks and latest additive technology, allowing high performance needed for the demanding requirements of passenger cars automatic gearboxes. This product can be used in a broad range of automatic transmissions and provides excellent service in a wide variety of North American, European and Asian vehicles. It is particularly suitable for 4 and 5 speed transmissions.

It is recommended for use in all GM vehicles calling for DII, DIII(G), DIII(H) specifications. It also exceeds the published JASO 1A, Ford M and Allison C-4 fluid specifications and transmissions recommending Toyota Type T-IV, amongst others.

Benefits

特典

- △ Provide excellent oxidation and thermal stability for longer life
- △ Superior wear protection to protect critical transmission components
- △ Excellent viscosity stability (high VI)
- △ Excellent friction and anti-shudder performance

Typical Characteristics

典型的な特徴

Test Description	Method	Unit	ICR- 5306
Density @ 15 °C	ASTM D 4052	kg/L	0.855
Flash Point	ASTM D 92	°C	200
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	33.44
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	7.262
Viscosity Index	ASTM D 2270	-	190

ICHIRO CORPORATION 株式会社

Furnishing the information contained herein does not constitute a representation by Ichiro that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Ichiro or any third party. Ichiro assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. Ichiro warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.

www.ichiro-oil.com

Specifications & Recommendations

仕様と推奨事項

△ ACURA	ATF-Z1
△ AISIN WARNER	JWS 3309 (T-IV), AW-1
△ ALLISON	C-3 & C-4
△ ALLISON	TES-389B
△ AMERICAN MOTORS	ATF +3 (MS7176-E)
△ ATF	RED 1, RED 1K
△ AUDI	5 HP LT71141 (ZF 5 HP 18FL/19FL/24A)
△ AUDI	G 052 025-A2
△ AUDI	G 055 025 A2 (JWS 3309)
△ AUDI	G 052 162-A1/A2 (ZF LIFEGUARDFLUID 5)
△ AUDI/VW	G 053 025-A2
△ AUDI/VW	052 055
△ AUDI/VW	G 052 990
△ BMW	JWS 3309 (T-IV)
△ BMW	LA2634
△ BMW	LT71141 (ZF 5 HP 18FL/19FL/24A)
△ BMW	ZF 5HP18FL, 5HP24, 5HP30
△ BMW	7045E
△ BMW	ETL-8072B
△ BMW	MINI
△ BMW	MINI 83 22 0 402 4132
△ BOSCH	TE-ML 09
△ CAT	TO-2
△ CHRYSLER	ATF+, +2, +3 (MS 7176E), 05127382AA
△ CHRYSLER/DODGE/JEEP	MOPAR AS 68 RC (T-IV), JWS 3309
△ CHRYSLER/DODGE	LT 71141
△ DAEWOO	AMMIX ATF D-II
△ DAIHATSU	AMMIX ATF D-III SP
△ ESSO	LT 71141
△ FIAT	T-IV TYPE, JWS 3309
△ FORD	MERCON®
△ FORD	FNR5
△ FORD	WSS M2C 138CJ, 166H
△ FORD	WSS M2C 922A1, 924A (XT-8-QAW) JWS 3309
△ FORD	XT-2-QDX (M)
△ FORD	XT-2-QSM (SYN)
△ FORD	ESP-M2C166H, XL-12

**ICHIRO**

Specifications & Recommendations

仕様と推奨事項

△ FUSO	ATF-II
△ FUSO	ATF-SP III
△ FUSO	ATF-A4
△ GM	9986195 AISIN AW, JWS 3309
△ GM	TASA
△ GM	DEXRON-II
△ GM	DEXRON-IID
△ GM	DEXRON-IIIE
△ GM	DEXRON-IIIG
△ GM	DEXRON-IIIH
△ GM	1940700
△ GM	1940767
△ GM	21005966
△ GM	22717466
△ GM	88900925
△ GM	93160393
△ GM/GMC/OPEL/SATURN	AW1
△ GM/GMC/OPEL/SATURN	88863400
△ GM/GMC/OPEL/SATURN	88863401
△ HINO	BLUE RIBON ATF
△ HONDA	ATF-Z1 (EXCEPT IN CVTS)
△ HYUNDAI/KIA	SP-III
△ HYUNDAI/KIA	DEX-II/ SP-II
△ HYUNDAI	SP-II M
△ HYUNDAI/KIA	JWS 3314
△ HYUNDAI/KIA	040000C90SG
△ IDEMITSU	K17 3100 PL085
△ ISUZU	BESCO ATF-II
△ ISUZU	BESCO ATF-III
△ JAGUAR	ATF 3403 M115
△ JAGUAR	ATF LT71141, ZF 5HP24
△ JAGUAR	ATF 3403 JLM20238
△ JAGUAR	JLM 20292
△ JASO	M315-2013 1A
△ JASO	M315-2013 2A
△ JEEP	ATF+3
△ LEXUS	JWS 3309
△ KIA	ATF SP-II, SP-III

Specifications & Recommendations

仕様と推奨事項

△ MAZDA	ATF D-II
△ MAZDA	ATF M-III
△ MAZDA	ATF M-V
△ MAZDA	ATF F-1
△ MAZDA	ATF S-1
△ MAZDA	ATF N-1
△ MAZDA	ATF 3317
△ MB	ZF 4HP20
△ MINI COOPER	T-IV
△ MITSUBISHI	DIAQUEEN SK
△ MITSUBISHI	DIAQUEEN SP
△ MITSUBISHI	DIAQUEEN SP-II
△ MITSUBISHI	DIAQUEEN SP-III
△ MITSUBISHI	DIAQUEEN AW
△ MITSUBISHI	DIAQUEEN J2
△ NAG	1 (CHRYSLER, JEEP, CHEROKEE)
△ NISSAN	MATIC FLUID C
△ NISSAN	MATIC FLUID D
△ NISSAN	MATIC FLUID J
△ NISSAN	MATIC FLUID K
△ OPEL/GM	19 40 700
△ OPEL/GM	19 40 767
△ OPEL/GM	21005966 TRANSAXLE
△ OPEL/GM	22 17466
△ OPEL/GM	88900925
△ OPEL/GM	9986195
△ PEUGEOT/CITROEN	Z 000169756
△ PEUGEOT/CITROEN	(PSA) AL4 AUTOMATIC GEARBOX OIL (#9730.AE)
△ PORSCHE	ZF 5HP19FL, ZF 5HP20, LT71141
△ PORSCHE	ATF 3403-M115,
△ PORSCHE	T-IV (JWS 3309)
△ PORSCHE	000 043 205 09
△ PORSCHE	999 917 547 00 (A2)
△ PORSCHE	000 043 205 28
△ PORSCHE	Z 000169756
△ PSA	
△ RENAULT	DPO/AL4
△ RENAULT	MATIC D2
△ RENAULT	SAMSUNG SATF-D

Specifications & Recommendations

仕様と推奨事項

△ SAAB	T-IV (JWS 3309)
△ SAAB	93 165 147
△ SAAB	93 160 393
△ SATURN	T-IV (JWS 3309)
△ SCION	(ALL VEHICLES)
△ SHELL	3403, M115, LA 2634
△ SUBARU	ATF
△ SUBARU	ATF 5AT
△ SUBARU	K0140Y0700
△ SUBARU	DEXRON®-II
△ SUBARU	ATF, ATF HP
△ SUZUKI	AT OIL 5D06
△ SUZUKI	ATF 2326
△ SUZUKI	ATF 2384K
△ SUZUKI	JWS 3309
△ SUZUKI	ATF 3314
△ SUZUKI	ATF 3317
△ TEXACO	7045-E
△ TEXACO	8072B
△ TEXACO	N402
△ TOYOTA	ATF D-II
△ TOYOTA	ATF D-III
△ TOYOTA	ATF T-III
△ TOYOTA	ATF T-IV
△ VICKERS	M2950-S, I-286-S
△ VOLVO	PN 1161521
△ VOLVO	97325
△ VOLVO	97335
△ VOLVO	CE 97340
△ VOLVO	PN 1161540/1161640
△ VW	G 052 055
△ VW	G-052 025 A2
△ VW	G-055-025 A2 (JWS 3309)
△ VW	G-052 162 (ZF LIFEGUARDFLUID 5)
△ VW	G US 000 162
△ ZF	ALL 3 & 4 SPEED TRANSMISSION
△ ZF	TE-ML 05L
△ ZF	TE-ML 09
△ ZF	TE-ML 21L

最後の変更: 25/6/2024
 整理番号: 4807G23ATFREV0