



PRODUCT DATA SHEET

ICHIRO

ICHIRO BYAKKO (ICR-5301)

Product Description:

Ichiro Byakko ICR-5301 is manufactured from highly refined base oils and chemical additives to meet a lot of passenger car or commercial vehicle performance demands, such as for Ford, General Motors, Mercedes Benz, Chrysler, Honda, Toyota, Mitsubishi, Nissan, Hyundai, Kia and so on. Ichiro Byakko ICR-5301 also meets Allison C-3 fluid and is qualified as a PSF, TASA specification.

Ichiro Byakko ICR-5301 is essential ashless thus lubricates and transmits the pressure needed for power-assisted steering with minimum sludge and deposit created. It's compatible to most hose and seal used in the power steering system. Ichiro Byakko ICR-5301 is recommended for power steering system, mobile equipment used by utility companies, hydraulic systems which require electrical insulating properties for their lubrication.

Applications / Benefits:

- Provides excellent friction, oxidation and thermal stability.
- Outstanding anti-wear properties.
- Improves hydrolytic stability.
- Better cold temperature flow properties than SAE 10W motor oil.

Typical Characteristics:

Test Description	Method	
Specific Gravity @ 15 °C	ASTM D 4052	0.858
Flash Point, °C	ASTM D 92	202
Pour Point , °C	ASTM D 97	-39
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	36.9
cSt @ 100°C	ASTM D 445	6.81
Viscosity Index	ASTM D 2270	145
Appearance	Visual	Red / Neutral

ICHIRO CORPORATION 株式会社

www.ichiro-oil.com

Furnishing the information contained herein does not constitute a representation by Ichiro that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Ichiro or any third party. Ichiro assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. Ichiro warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTS relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.



PRODUCT DATA SHEET

ICHIRO

Specifications, Approvals & Recommendations:

• Chrysler MS-1872	SFU
• Chrtslr MS-5931, P/N 04883077	SFU
• Ford M2C195-A	SFU
• GM P/N 89021184	SFU
• GM 9985010, P/N 1052884	SFU
• Hyundai PSF-3	SFU
• Kia PSF-3	SFU
• MB 236.3, P/N 000 989 88 03	SFU
• Mitsubishi PS Fluid	SFU
• Mitsubishi Diamond SP III	SFU
• Nissan PSF-II	SFU
• Saab P/N (45) 30 09 800	SFU
• Subaru P/N K0209A0080	SFU
• Toyota PSF Type EH, P/N 008886-01	SFU

ICHIRO CORPORATION 株式会社

www.ichiro-oil.com

Furnishing the information contained herein does not constitute a representation by Ichiro that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Ichiro or any third party. Ichiro assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. Ichiro warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.