



# PRODUCT DATA SHEET

## ICHIRO

### ICHIRO BYAKKO (ICR-5304)

#### Product Description:

Ichiro Byakko ICR-5304 is a premium synthetic automatic transmission fluid. It is formulated with selected high viscosity index synthetic base stocks and latest additive technology available allowing very high performance needed for the demanding requirements of passenger cars automatic gearboxes. Ichiro Byakko ICR-5304 can be used in a broad range of automatic transmission standards and provides excellent service in a wide variety of North American, European, and Asian vehicles. It's particularly suitable for 4 and 5 speeds automatic transmissions.

Ichiro Byakko ICR-5304 is recommended for use in all GM vehicles DII, DIII(G), DIII(H). It exceeds the published JASO 1A, Ford M and Allison C-4 fluid specifications and suitable for use in automatic transmission recommending Toyota Type T-IV.

#### Applications / Benefits:

- Provides excellent oxidation and thermal stability for longer life.
- Superior wear protection to protect critical transmission components.
- Excellent viscosity stability(high VI), application in a wide variety of Auto Transmission.
- Excellent friction and anti-shudder performances, improve driver's comfort with smooth and efficient shifting.
- Much enhanced fluidity at very low temperature service.
- Excellent rust and corrosion protection.

#### Typical Characteristics:

Test Description	Method	
Specific Gravity @ 15 °C	ASTM D 4052	0.853
Flash Point, °C	ASTM D 92	198
Pour Point , °C	ASTM D 97	-45
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	38.1
cSt @ 100°C	ASTM D 445	7.24
Viscosity Index	ASTM D 2270	157
Appearance	Visual	Red

#### Specifications, Approvals & Recommendations:

ATF T-IV

SFU

ICHIRO CORPORATION 株式会社

[www.ichiro-oil.com](http://www.ichiro-oil.com)

Furnishing the information contained herein does not constitute a representation by Ichiro that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Ichiro or any third party. Ichiro assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. Ichiro warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTS relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.