



PRODUCT DATA SHEET

ICHIRO

ICHIRO BYAKKO (ICR-5407)

Product Description:

Ichiro Byakko ICR-5407 is a premium synthetic automatic transmission fluid. It is formulated with selected synthetic base stocks and latest additive technology available that provides excellent service in applications calling for low viscosity ATF, such as: Toyota Type WS.

Synthetic base stocks and stability of Ichiro Byakko ICR-5407 protects against thermal breakdown at high operating temperatures, while still providing outstanding performance at ambient temperatures as low as -45° C. Moreover, it improves overall transmission durability and cleanliness.

Applications / Benefits:

- Provides excellent oxidation and thermal stability for longer life.
- Superior wear protection to protect critical transmission components.
- Excellent viscosity stability(high VI), application in low viscosity Auto Transmission.
- Much enhanced fluidity at very low temperature.
- Excellent rust and corrosion protection.

Typical Characteristics:

Test Description	Method	
Specific Gravity @ 15 °C	ASTM D 4052	0.845
Flash Point, °C	ASTM D 92	198
Pour Point , °C	ASTM D 97	-45
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	26.72
cSt @ 100°C	ASTM D 445	5.66
Viscosity Index	ASTM D 2270	160
Appearance	Visual	Red

Specifications, Approvals & Recommendations:

- Toyota / Lexus / Scion Type WS SFU

SFU = Suitable for Use

ICHIRO CORPORATION 株式会社

www.ichiro-oil.com

Furnishing the information contained herein does not constitute a representation by Ichiro that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of Ichiro or any third party. Ichiro assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. Ichiro warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.