

ICHIRO BYAKKO ICR-4327

AUTOMOTIVE GEAR - API GL4/5

Description

説明

Synthetic multipurpose gear oil produced from selected premium base oil and blended with Total Driveline (TDL) additives. This combination results in a product with exceptional chemical and thermal stability and ensure vehicles keep driven on the road longer.

This product provides a solution that extends seal life, enhances synchronizer performance, and improves durability for the axle and transmission at a excellent level. It delivers superior seal protection and outstanding synchronizer performance as well as capable with API GL-5 specifications.

Benefits

特典

- △ Improves hardware reliability and save costs
- △ Reduces downtime from synchronizer failure
- △ Higher thermal stability reduces deposit formation and damage
- △ Provides superior seal protection

Typical Characteristics

典型的な特徴

Test Description	Method	Unit	ICR-
			4327
SAE Viscosity Grade	SAE J 300	-	75W90
Density @ 15 °C	ASTM D 4052	kg/L	0.878
Flash Point	ASTM D 92	°C	210
Pour Point	ASTM D 97	°C	-36
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	81.6
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	15.6
Viscosity Index	ASTM D 2270	-	204

Suggested for the Following Uses**以下の用途におすすめ**

△ API	GL-5
△ API	GL-4
△ DAF	SFU
△ IVECO	SFU
△ SCANIA	STO 1:0
△ SCANIA	STO 1:1 G
△ ZF	TE-ML 07A
△ ZF	TE-ML 24A
△ ZF	TE-ML 04G
△ ZF	TE-ML 08

最後の変更: 02-09-25

整理番号: 6415G23GL4GL5REV0